

**Slide Media In...**



**Degaussed  
Media Slides Out.**

- Portable.
- Continuous Duty.
- 10 Second Erasure Cycle.
- Operates on standard wall outlet.
- Complete Erasure of High Coercivity Hard Drives & Tape.



Optional Shipping / Transportation case minimizes data liability by transporting the degausser to the secure location of the media rather than risking the loss of data through transportation.

The HD-3W is the newest and most innovative product in the Garner line of degaussers. The HD-3W erases hard drives and high coercivity tape media including all formats of LTO (1, 2, and 3), SuperDLT I & II, DLT, 9940, 3592, AIT, 8mm and more, all without any adapters. With a continuous duty rating (no cooling necessary) and 13 second cycle time, even large quantities of media can be erased in a very short period of time.

### HD-3W Operations:

The HD-3W is exceptionally user-friendly. Simply slide your media into the slot on the left side of the HD-3W and push the "Erase" button. Within two seconds your media will be completely erased and will automatically slide out the right side of the HD-3W. It just doesn't get any easier than that! If space is at a premium, the compact design of the HD-3W occupies just over one square foot.

### Degauss vs. Overwrite:

The HD-3W produces an erasing field many times stronger than the erasing fields produced by the read/write heads in hard drives and tape drives. The field strength along with the encompassing magnetic field ensure the data is no longer recoverable by computer or laboratory attacks. Since

the HD-3W does not rely on software, the HD-3W will also completely and permanently erase failed and damaged hard drives regardless of the operating system or interface.

### Government Mandates:

The HD-3W will assist you in meeting compliance standards for government mandates requiring complete elimination of sensitive information stored on magnetic media prior to re-use or disposal including:

- **PCI DSS** (Payment Card Industry) Data Security Standard
- **NIST** (National Institute of Standards and Technology) Guidelines for Media Sanitization
- **NIST SP 800-36**
- **NIST SP 800-88**
- **HIPAA** (Health Information Portability and Accountability Act)
- **PIPEDA** (Personal Information Protection and Electronic Documents Act)
- **GLBA** (Gramm-Leach-Bliley Act)
- **California Senate Bill 1386**

SPECIFICATIONS	
Power Supply	120V ±5%, 50/60 Hz - Standard
Power Consumption	Under standby 0.2A While charging 8.0A At the time of ERASE 0.5A
Degausser System	Capacitive Discharge
Operating Time	<b>Duty Cycle:</b> Continuous
Cycle time	10 seconds
Magnetic Field	8,500 Oe, .85 Tesla
Max. Media Size	6.75 in. (W) x 4.5 in. (H) x 1.3 in. (D)
Erasing Area Size	6.75 in. (W) x 4.5 in. (H) x 1.3 in. (D)
Media	2.5 type HDD, 3.5 type HDD, DLT, LTO, 3490 formfactors and more
Temperature	41°F - 104°F (5°C - 40°C)
Humidity	10%H - 40%H (without condensation)
Weight	<b>HD-3W:</b> 75 lbs. (25 Kg) <b>Shipping:</b> 95 lbs. (37.64 Kg)
Size	<b>HD-3W:</b> 12.25 in. (L) x 13.125 in. (W) x 18.75 in. (H) without slide 12.25 in. (L) x 22.625 in. (W) x 18.75 in. (H) with slide
Warranty	1 Year Factory Warranty Standard, Optional 3 Year Factory Warranty available.
Note	Hard Drives are not reusable after having been erased.